

## Wall Legendz Installation Instructions

- Pick a LOCATION. WALL LEGENDZ adhere well to smooth, indoor surfaces. Recommended and NOT recommended surfaces are listed below. You want to choose a RECOMMENDED surface.
- Measure the area to make sure your WALL LEGENDZ will fit.
- Lay flat for an hour prior to application to allow WALL LEGENDZ to adjust to room temperature and unroll.
- Use a warm damp cloth to wipe down the surface and let it dry completely. DO NOT use soap or cleaning agents. They can make your WALL LEGENDZ stick poorly.
- Start at the top of your WALL LEGENDZ and carefully peel it from its backing.
- Place one corner on the wall and slowly smooth the rest into place using minimal pressure. If you make a mistake, gently peel the WALL LEGENDZ off the wall and reposition it.
- Once positioned, use a credit card, drivers license or similar flat object and gently apply pressure to the WALL LEGENDZ to remove any air pockets or wrinkles.
- Keep the backing in case you want to move to a new location later.

### **Recommended Surfaces:**

- Smooth Walls
- Painted Drywall
- Glass
- Metal
- Inside, temperature controlled environments

### **NOT Recommended Surfaces:**

- Freshly painted walls. Wait at least 30 days after painting.
- Textured Walls
- Unpainted drywall
- Brick
- Cinder Block
- Porous, textured paneling
- Outside, non-temperature controlled environments

[www.graphixunlimited.com](http://www.graphixunlimited.com)